



### *Confirmation of Product Type Approval*

Please refer to the "Service Restrictions" shown below to determine if Unit Certification is required for this product. This certificate reflects the information on the product in the ABS Records as of the date and time the certificate is printed.

Pursuant to the Rules of the American Bureau of Shipping (ABS), the manufacturer of the below listed product held a valid Manufacturing Assessment (MA) with expiration date of 03-MAR-2024. The continued validity of the Manufacturing Assessment is dependent on completion of satisfactory audits as required by the ABS Rules.

And; a Product Design Assessment (PDA) valid until subject to continued compliance with the Rules or standards used in the evaluation of the product.

The above entitle the product to be called Product Type Approved.

The Product Design Assessment is valid for products intended for use on ABS classed vessels, MODUs or facilities which are in existence or under contract for construction on the date of the ABS Rules used to evaluate the Product.

ABS makes no representations regarding Type Approval of the Product for use on vessels, MODUs or facilities built after the date of the ABS Rules used for this evaluation.

Due to wide variety of specifications used in the products ABS has evaluated for Type Approval, it is part of our contract that; whether the standard is an ABS Rule or a non-ABS Rule, the Client has full responsibility for continued compliance with the standard.

**Product Name: Pump**  
**Model Name(s): HXL 6", 8" & 10" Series**

**Presented to:**  
BLACKMER, A DOVER RESOURCES COMPANY  
1809 CENTRY AVENUE  
MI 49509  
United States

<b>Intended Service:</b>	Marine & Offshore Application - Transfer and Stripping pumps for AFFF (Foam), Clean Distillate and Heavy Fuels, Lubes, Oil, Dirty Distillate and Heavy Oils.
<b>Description:</b>	Sliding Vane Pumps constructed with Ductile Iron (ASTM 536, 18% Elongation).
<b>Tier:</b>	5
<b>Ratings:</b>	Performance Data: HXL 6 Series: Capacity to 90 to 755 GPM; Speed: 45 to 350 RPM; Power capacity: 10 to 30 HP HXL 8 Series: Capacity to 145 1200 GPM; Speed: 45 to 350 RPM; Power capacity: 15 to 45 HP HXL 10 Series: Capacity to 430 to 2220 GPM; Speed:45 to 230 RPM; Power capacity: 38 to 97 HP Maximum Operating Limits: HXL 6 Series: Flow rate capacity: 755 GPM Pump Speed: 350 rpm Maximum Working Pressure: 150 psi (10.3 bar) Maximum Differential Pressure: 125 psi (8.6 bar) Maximum Temperature: 400 °F (204 °C) HXL 8 Series: Flow rate capacity: 1200 GPM Pump Speed: 350 rpm Maximum Working Pressure: 250 psi (17.2 bar) Maximum Differential Pressure: 150 psi (10.3 bar) Maximum Temperature: 400 °F (204 °C) HXL 10 Series: Flow rate capacity: 45 to 2,220 GPM Pump Speed: 230 rpm Maximum Working Pressure: 250 psi (17.2 bar) Maximum Differential Pressure: 150 psi (10.3 bar) Maximum Temperature: 400 °F (204 °C) See "pdf" attachment for Performance Curves.
<b>Service Restrictions:</b>	Unit Certification is required for this product if the pumps are used for services listed in Marine Vessels Rules 4-6-1/7.3.1, hydrostatic and capacity testing is to be performed to the satisfaction of the Surveyor as indicated in Marine Vessels Rules

4-6-1/7.3.2 a), b).

**Comments:** The Manufacturer has provided a declaration about the control of, or the lack of Asbestos in this product.

**Notes / Documentation:** Supporting Documentation: BLACKMER HXL DIMENSIONS BLACKMER HXL PARTS LIST DWG Model HXL - DWG Model HXL HXL\_MATERIALS\_SHEET-MATERIALS OF CONSTRUCTION MODELS: HXL6G HXL8G HXLJ8G HXL10E-102-091 Effective December 2015 HXL\_SPEC\_SHEET- HXL SERIES SHOCK-RESISTANT DUCTILE IRON PUMPS- 102-001 Effective June 2015 HXL\_CURVES\_SHEET - CHARACTERISTIC CURVES MODELS: HXL6-102-021 Effective October 2013

**Term of Validity:** This Product Design Assessment (PDA) Certificate 19-HS1825396-PDA, dated 04/Mar/2019 remains valid until 03/Mar/2024 or until the Rules or specifications used in the assessment are revised (whichever occurs first). This PDA is intended for a product to be installed on an ABS classed vessel, MODU or facility which is in existence or under contract for construction on the date of the ABS Rules or specifications used to evaluate the Product. Use of the Product on an ABS classed vessel, MODU or facility which is contracted after the validity date of the ABS Rules and specifications used to evaluate the Product, will require re-evaluation of the PDA. Use of the Product for non ABS classed vessels, MODUs or facilities is to be to an agreement between the manufacturer and intended client.

**ABS Rules:** 2019 ABS Marine Vessels Rules 1-1-4/7.7, 1-1-A3, 1-1-A4, 4-6-1/7.3.1, 4-6-1/7.3.2 2019 ABS Mobile Offshore Units Rules 1-1-4/9.7, 1-1-A2, 1-1-A3, 4-2-2/3

**National Standards:**  
**International Standards:**  
**Government Authority:**  
**EUMED:**  
**Others:**

Model Certificate	Model Certificate No	Issue Date	Expiry Date
PDA	19-HS1825396-PDA	04-MAR-2019	03-MAR-2024

ABS Programs

ABS has used due diligence in the preparation of this certificate and it represents the information on the product in the ABS Records as of the date and time the certificate was printed. Type Approval requires Drawing Assessment, Prototype Testing and assessment of the manufacturer's quality assurance and quality control arrangements. Limited circumstances may allow only Prototype Testing to satisfy Type Approval. The approvals of Drawings and Products remain valid as long as the ABS Rule, to which they were assessed, remains valid. ABS cautions manufacturers to review and maintain compliance with all other specifications to which the product may have been assessed. Further, unless it is specifically indicated in the description of the product; Type Approval does not necessarily waive witnessed inspection or survey procedures (where otherwise required) for products to be used in a vessel, MODU or facility intended to be ABS classed or that is presently in class with ABS. Questions regarding the validity of ABS Rules or the need for supplemental testing or inspection of such products should, in all cases, be addressed to ABS.