



Hygienic

Hygienic and FDA Series

Air-Operated Double-Diaphragm Pumps




Purity.
Performance.
Purpose.

WILDEN®

Hygienic and FDA Series Solutions

As the global leader in sanitary, hygienic and biopharmaceutical air-operated double-diaphragm (AODD) pumps, Wilden® offers a wide range of solutions for food, beverage, pharmaceutical and personal care applications. These solutions – which include Hygienic Series (HS) and FDA Series pumps – have been engineered to meet or exceed the highest standards and requirements in the industry, including 3-A, FDA CFR 21.177, 1935/2004/EC, USP Class VI*, ATEX, and CE.

Wilden Hygienic and FDA Series pumps have the versatility you require, the safety you need, and the capability of efficiently pumping an array of viscosities, solids and shear-sensitive products. They are offered with passivated 316L stainless steel and Alloy C components and are available in multiple sizes and with various surface finishes. All Hygienic and FDA Series pumps have clamped connections for easy assembly and disassembly, and clean-in-place (CIP)** and clean-out-of-place (COP) capabilities.



*USP Class VI certification available only on Hygienic Series pumps with PTFE elastomer options
 **Hygienic Series pumps only



FOOD AND BEVERAGE



PREPARED FOOD AND SAUCES



POULTRY AND DAIRY



SWEETENERS AND ACIDS




PHARMACEUTICAL AND COSMETICS



Wilden Pumps vs. Competing Technologies

AODD Pumps



Wilden pumps use air pressure and suction to delicately move liquids and solids. Thanks to this unique operating principle, our AODD pumps are ideal for the hygienic transfer of shear-sensitive products. Benefits include:

- Self priming
- Shear-sensitive
- High vacuum pressure
- Superior product containment


Low-Shear Hygienic and FDA Series Pumps Protect Product Integrity

Hygienic and FDA Series AODD pumps are among the safest, gentlest transfer technologies for hygienic applications. They operate by drawing product into a chamber and gentle pushing it back out, ensuring no contact with moving parts. This low-shear operation ensures products are not damaged or compromised.




With Shear-Sensitive Operation

Competing Technologies May Damage Shear-Sensitive Products



Lobe

- Less mechanically effective
- Unable to strip lines
- Higher product shear
- Reduced flow capacity



Centrifugal

- Not self-priming
- Difficulty handling higher-viscosity liquids
- Utilize mechanical seals that can lead to costly leaks



Without Shear-Sensitive Operation

Wilden Hygienic Series Pumps: One-Of-A-Kind Design

Hygienic Series pumps are uniquely designed to meet high cleanliness requirements, with a free-draining flow path that enables clean-in-place (CIP) capability while lowering the risk of product contamination.

Free-Draining Flow Path

Hygienic Series have been specifically designed for superior drainability thanks to the free-draining flow path. The pumps can quickly and easily be drained without the need to disassemble the pump. With these state-of-the-art design features that help simplify cleaning, Hygienic Series pumps are the only US-manufactured pumps in the industry to have earned 3A certifications for CIP operations

Offset checks for ease of assembly

Flow-through design for CIP applications and improved shear sensitivity

Competitor


Catch area for product to settle in flow path

Wilden

Product completely drains from flow path

Tri-Clamp®


Pump performance can be further optimized through the use of patented Tri-clamp®-style fittings that have been designed with an eccentric cartridge check valve assembly, allowing for ease of maintenance by ensuring liquid chambers and pump manifold alignment. HS pumps also feature wash-friendly clamp bands with wetted path material of 316L stainless steel or alloy C with an Ra 0.8 µm (32 µ-in) interior polish for ease of cleaning. DIN and SMS connections also available.



Tri-Clamp®




Discharge



Three different valve options available to best suit your specific application.

State-of-the-art design keeps food from being captured




Inlet

CIP swivel stand for ease of cleaning and draining

Hygienic Series Valve Options


Most Hygienic Series pumps come standard with ball valves, but other valve options are available to customize for your specific application.

	BALL VALVE	FLAP VALVE	MUSHROOM VALVE
BEST FOR:	Shear Sensitive Items	Large Solids	Viscous Products
EXAMPLES:	Noodles Fruit preserves Grapes for wine Salsa	Poultry Eggs Meat products Waste	Peanut butter Molasses Ketchup Gels and creams



CIP Stand

For ease of maintenance and cleaning, Wilden offers an optional swivel pump to be drained by rotating the pump so that the fluid can flow out of the discharge and into a suitable container. The swivel stand also permits the pump to be drained without disassembly.






Wilden FDA Series Pumps

FDA Series pumps offer the flexibility to safely, reliably and efficiently perform across a wide range of viscosities. Their AODD design enables low-shear operation that protects the integrity of delicate, shear-sensitive products. With simple installation and robust durability, FDA Series pumps incorporate a straight flow-through design, large solids passage and Tri-clamp®-style fittings.

Ideal for standard food applications, FDA Series pumps are designed for ease of use and maintenance with clean-out-of-place (COP) capabilities. The wetted path material is 316L stainless steel or alloy C with Ra 5.1 µm (200 µin) surface finish for ease of cleaning.



Pump Selection Guide for Sanitary and Hygienic Applications

	PUMP LIQUID INLET	AIR DISTRIBUTION SYSTEM	CLEANING METHOD	SANITARY APPLICATION RANGE	PRODUCT EXAMPLE	POLISH LEVELS Ra $\mu\text{-m}$ ($\mu\text{-inch}$)	CERTIFICATIONS
Hygienic Series 	25 mm (1") 38 mm (1-1/2") 51 mm (2") 76 mm (3")	Pro-Flo SHIFT	CIP/COP	Low Acid, Pasteurized & Protein-Based Products	Milk Meat Egg Vegetable-Based Products Personal Care Products	Ra 0.8 μm (32 $\mu\text{-in}$)	    
High Pressure Hygienic Series 	76 mm (3")	High Pressure	CIP/COP	Cosmetics, Viscous Products	Creams Shampoo Soaps Lotion	Ra 0.8 μm (32 $\mu\text{-in}$)	   
Hygienic Series (Pharma) *RR Only 	38 mm (1-1/2") 51 mm (2") 76 mm (3")	Pro-Flo SHIFT	CIP/COP	Biopharmaceutical Sterile Process	Active Pharmaceutical Ingredients Cosmetics Live Cultures	Ra 0.35 μm (14 $\mu\text{-in}$)	    
FDA Series 	25 mm (1") 38 mm (1-1/2") 51 mm (2") 63 mm (2-1/2") 76 mm (3")	Pro-Flo & Pro-Flo SHIFT	COP	High Acid, High Sugar, High Fat Food	Sweeteners Icings Juices Fruit Ingredients Some Sauces	Ra 5.1 μm (200 $\mu\text{-in}$)	   
Stallion & Brahma 	38 mm (1-1/2")* 51 mm (2") 76 mm (3")	Pro-Flo SHIFT	N/A	Non-Sanitary Waste	Process Wastes Large Solid	N/A	 
Bolted Plastic 	6 mm (1/4") 13 mm (1/2") 25 mm (1") 38 mm (1-1/2") 51 mm (2") 76 mm (3")	Pro-Flo & Pro-Flo SHIFT	N/A	Non-Sanitary Waste, Chemical Cleaning Process	CIP Chemicals	N/A	 

* Stallion Only

Progressive Diaphragm Technology

Pure-Fuse Diaphragms


Pure-Fuse Integral Piston Diaphragms are the ideal solution for food and pharmaceutical applications. Pure-Fuse integral piston one piece design that eliminates trap areas between the outer piston and the diaphragm. This design also eliminates the normal abrasive wear caused by the outer piston in a conventional configuration, resulting in a longer-lasting diaphragm. Additionally, Pure-Fuse offers clean-in-place (CIP) capability, superior flow and suction lift over competitor IPDs.

- Up to 100% increased flow and suction lift compared to PTFE laminate diaphragms
- Eliminates trap areas between outer piston and diaphragm where bacteria can grow
- Eliminates normal abrasive wear caused by the outer piston in a conventional configuration, resulting in longer diaphragm life
- Easy cleanability for faster changeovers between product
- Up to 50% price reduction compared to PTFE laminate diaphragms
- No adhesive used in the diaphragm construction unlike competitive one-piece diaphragms
- Sanitary materials meet FDA CFR 21.177, 3-A requirements, and 1935/2004/EC*




STANDARD DIAPHRAGM

GOOD
★★★★☆



PURE-FUSE DIAPHRAGM

BEST
★★★★★



Thermoplastic (TPE) Diaphragms

TPE diaphragms are durable, low cost and effective across a wide temperature range.

Wilden TPE diaphragm options include Wil-Flex™ and Saniflex™. These diaphragms are injection-molded of man-made elements and have inherent tensile strength without the need for fabric reinforcement.

Versions of Wil-Flex and Saniflex are available that comply with FDA CFR 21.177 standards for food and beverage applications.

PTFE Diaphragms

Wilden PTFE diaphragms feature a full-stroke or a reduced-stroke design depending on required performance. PTFE complies with FDA CFR 21.177 and USP Class VI standards for food, beverage and pharmaceutical applications. Because PTFE is non-elastic, a backup diaphragm of a different material must be used to provide flexibility and memory. Material options for backup diaphragms include Wil-Flex, Saniflex, Neoprene and high temperature Buna-N.

Hygienic & Sanitary Accessories

Surge Dampeners

Wilden Equalizer® Surge Dampeners, Hygienic SD Series, minimize unwanted pressure fluctuations by providing a supplementary pumping action to virtually eliminate pressure variation and pulsation on AODD pumps. The Equalizer automatically sets and maintains the correct air pressure matching the variations in liquid flow or discharge pressure generated by the pump. They meet FDA, EHEDG and USP Class VI standards when configured with PTFE integral-piston diaphragms. They also meet ATEX requirements for use in explosive environments. Available in 38 mm (1-1/2"), 51 mm (2") and 76 mm (3") sizes.



Electronic Accessories

Wil-Gard™: Detects and notifies plant personnel when a diaphragm has ruptured to prevent further damage to pump.

Pump Cycle Monitor (PCMI): Counts pump cycles by sensing the presence of the air valve spool.



Repair and Retrofit Kits

Wilden wet and air repair kits for AODD pumps have been designed to help properly maintain the health and performance of your Wilden pump.

Always use only authentic Wilden air kits and wet kits when repairing or maintaining your Wilden products to preserve optimal performance and factory warranties.

- Easily order online at your convenience
- Kits are maintained and shipped in sealed packaging
- Include all necessary components for repair and maintenance


Wilden also offers retrofit kits which allow you to upgrade your existing pumps. Other spare parts outside of the traditional repair kits are available upon request.




Pro-Flo® SHIFT Air Distribution System

The Wilden Pro-Flo SHIFT is the premier air distribution system. The innovative, yet simple, Pro-Flo SHIFT design features an air control spool that automatically optimizes air consumption and eliminates the overcharging of the air chamber with no reduction in flow rate. This results in a reduction of air consumption and operational costs while maintaining maximum operational efficiency and volumetric consistency.

- Fewer operating parts, meaning less downtime and simplified maintenances
- Delivers more yield per SCFM versus competitive AODD pumps
- Longer diaphragm life
- Quiet operation




CE



Pro-Flo® Air Distribution System

The secret to the success of Pro-Flo Series pumps is the incorporation of a simple and durable Air Distribution System (ADS) that features a plastic center block and lube-free operation. The patented Pro-Flo ADS incorporates three moving parts: the unbalanced air valve spool, the pilot spool and the main shaft/diaphragm assembly for simplicity and high reliability.





25 mm (1") PRO-FLO SHIFT HYGIENIC SERIES METAL PUMP

Air Inlet: 1/2" FNPT
Tri-Clamp Inlet: 25 mm (1")
Tri-Clamp Discharge: 25 mm (1")
Valve Options: Ball




Max. Flow Rate:
121 lpm (32 gpm)
Max. Inlet Pressure:
8.6 bar (125 psig)
Max. Size Solids:
6.4 mm (1/4")

Max. Suction Lift:
3.9 m Dry (13')
7.9 m Wet (26')
Shipping Weight:
316L Stainless Steel 40 kg (88 lb)
Alloy C 44 kg (97 lb)


PS2 HYGIENIC SERIES

Dimensions



Note that dimensions vary by connection, material and stand option. For additional information, please refer to the PS2 Hygienic Series EOM.

Flow Curve FULL-STROKE INTEGRAL PISTON DIAPHRAGM-FITTED



38 mm (1-1/2") PRO-FLO SHIFT HYGIENIC SERIES METAL PUMP

Air Inlet: 3/4" FNPT
Tri-Clamp Inlet: 38 mm (1-1/2")
Tri-Clamp Discharge: 38 mm (1-1/2")
Valve Options: Ball, Mushroom




Max. Flow Rate:
357 lpm (94 gpm)
Max. Inlet Pressure:
8.6 bar (125 psig)
Max. Size Solids:
Ball Valve 12.7 mm (1/2")
Mushroom Valve 6.4 mm (1/4")

Max. Suction Lift:
5.4 m Dry (17.6')
9.0 m Wet (29.5')
Shipping Weight:
316L Stainless Steel 51 kg (112 lb.)
Alloy C 56 kg (123 lb.)


PS4 HYGIENIC SERIES


Dimensions



Note that dimensions vary by connection, material and stand option. For additional information, please refer to the PS4 Hygienic Series EOM.

Flow Curve FULL-STROKE INTEGRAL PISTON DIAPHRAGM-FITTED





PS8 HYGIENIC SERIES

51 mm (2") PRO-FLO SHIFT HYGIENIC SERIES METAL PUMP


Air Inlet: 3/4" FNPT
Tri-Clamp Inlet: 51 mm (2")
Tri-Clamp Discharge: 51 mm (2")
Valve Options: Ball, Flap, Mushroom



Max. Flow Rate:
575 lpm (152 gpm)
Max. Inlet Pressure:
8.6 bar (125 psig)
Max. Size Solids:
Ball Valve 12.7 mm (1/2")
Flap Valve 47.5 mm (1-7/8")
Mushroom Valve 6.4 mm (1/4")



Max. Suction Lift:
4.1 m Dry (13.6')
9.0 m Wet (29.5')
Shipping Weight:
316L Stainless Steel 49 kg (108 lb)
Alloy C 54 kg (119 lb)

Dimensions



Note that dimensions vary by connection, material and stand option. For additional information, please refer to the PS8 Hygienic Series EOM.

Flow Curve FULL-STROKE INTEGRAL PISTON DIAPHRAGM-FITTED



PS15 HYGIENIC SERIES

76 mm (3") PRO-FLO SHIFT HYGIENIC SERIES METAL PUMP


Air Inlet: 3/4" FNPT
Tri-Clamp Inlet: 76 mm (3")
Tri-Clamp Discharge: 76 mm (3")
Valve Options: Ball, Flap, Mushroom



Max. Flow Rate:
844 lpm (223 gpm)
Max. Inlet Pressure:
8.6 bar (125 psig)
Max. Size Solids:
Ball Valve: 19.1 mm (3/4")
Flap Valve: 60.3 mm (2-3/8")
Mushroom Valve: 9.5 mm (3/8")


Max. Suction Lift:
4.4 m Dry (14.4')
9.0 m Wet (29.5')
Shipping Weight:
316L Stainless Steel 98 kg (216 lb)
Alloy C 108 kg (238 lb)


Dimensions



Note that dimensions vary by connection, material and stand option. For additional information, please refer to the PS15 Hygienic Series EOM.

Flow Curve FULL-STROKE INTEGRAL PISTON DIAPHRAGM-FITTED





76 mm (3") HIGH PRESSURE HYGIENIC SERIES METAL PUMP

Air Inlet 3/4" FNPT
Tri Clamp Inlet: 76 mm (3")
Tri-Clamp Discharge: 76 mm (3")
Valve Options: Ball, Mushroom




Max. Flow Rate:
291 lpm (77 gpm)
Max. Inlet Pressure:
8.6 bar (125 psig)
Max. Size Solids:
6.4 mm (1/4")

Max. Suction Lift:
3.8 m Dry (12.5')
9.0 m Wet (29.5')
Shipping Weight:
115 kg (254 lb)



H1500 HYGIENIC SERIES

Dimensions



Note that dimensions vary by connection, material and stand option. For additional information, please refer to the H1500 Hygienic Series EOM.

Flow Curve FULL-STROKE INTEGRAL PISTON DIAPHRAGM-FITTED



PS1 FDA SERIES

13 mm (1/2") PRO-FLO SHIFT FDA SERIES METAL PUMP


Air Inlet: 1/2" FNPT
Tri-Clamp Inlet: 25 mm (1")
Tri-Clamp Discharge: 25 mm (1")




Max. Flow Rate:
60.2 lpm (15.9 gpm)
Max. Inlet Pressure:
8.6 bar (125 psig)
Max. Size Solids:
1.6 mm (1/16")

Max. Suction Lift:
5.9 m Dry (19.3')
9.8 m Wet (32.3')
Shipping Weight:
9 kg (20 lb)


Dimensions



Flow Curve TPE-FITTED



For additional information, please refer to the PS1 Metal EOM.



PS4 FDA SERIES



Air Inlet: 3/4" FNPT
Tri-Clamp Inlet: 51 mm (2")
Tri-Clamp Discharge: 51 mm (2")




Max. Flow Rate:
375 lpm (99 gpm)
Max. Inlet Pressure:
8.6 bar (125 psig)
Max. Size Solids:
4.8 mm (3/16")

Max. Suction Lift:
7.1 m Dry (23.3')
8.6 m Wet (28.4')
Shipping Weight:
28 kg (62 lb)


Dimensions



Flow Curve EZ-INSTALL TPE-FITTED



Note that dimensions vary by material. For additional information, please refer to the PS4 Metal EOM.



PS8 FDA SERIES



Air Inlet: 3/4" FNPT
Tri-Clamp Inlet: 64 mm (2-1/2")
Tri-Clamp Discharge: 64 mm (2-1/2")




Max. Flow Rate:
723 lpm (191 gpm)
Max. Inlet Pressure:
8.6 bar (125 psig)
Max. Size Solids:
6.4 mm (1/4")

Max. Suction Lift:
7.2 m Dry (23.8')
9.0 m Wet (29.5')
Shipping Weight:
53 kg (117 lb)


Dimensions



Flow Curve EZ-INSTALL TPE-FITTED



Note that dimensions vary by material. For additional information, please refer to the PS8 Metal EOM.



PS15 FDA SERIES

76 mm (3") PRO-FLO SHIFT FDA SERIES METAL PUMP



Air Inlet: 3/4" FNPT
Tri-Clamp Inlet: 76 mm (3")
Tri-Clamp Discharge: 76 mm (3")




Max. Flow Rate:
927 lpm (245 gpm)
Max. Inlet Pressure:
8.6 bar (125 psig)
Max. Size Solids:
9.5 mm (3/8")

Max. Suction Lift:
6.6 m Dry (21.6')
8.6 m Wet (28.4')
Shipping Weight:
105 kg (230 lb)


Dimensions



Flow Curve EZ-INSTALL TPE-FITTED



Note that dimensions vary by material. For additional information, please refer to the PS15 Metal EOM.



P1 FDA SERIES

13 mm (1/2") PRO-FLO FDA SERIES METAL PUMP



Air Inlet: 1/4" FNPT
Tri-Clamp Inlet: 25 mm (1")
Tri-Clamp Discharge: 25 mm (1")




Max. Flow Rate:
58.7 lpm (15.5 gpm)
Max. Inlet Pressure:
8.6 bar (125 psig)
Max. Size Solids:
1.59 mm (1/16")

Max. Suction Lift:
5.8 m Dry (19.0')
9.5 m Wet (31.0')
Shipping Weight:
9 kg (20 lb)


Dimensions



Flow Curve TPE-FITTED



For additional information, please refer to the P1 Metal EOM.



P2 FDA SERIES

25 mm (1") PRO-FLO FDA SERIES METAL PUMP


Air Inlet: 1/4" FNPT
Tri-Clamp Inlet: 38 mm (1-1/2")
Tri-Clamp Discharge: 38 mm (1-1/2")




Max. Flow Rate:
172 lpm (45.5 gpm)
Max. Inlet Pressure:
8.6 bar (125 psig)
Max. Size Solids:
3.2 mm (1/8")

Max. Suction Lift:
7.6 m Dry (25.0')
9.0 m Wet (29.5')
Shipping Weight:
17 kg (37 lb)


Dimensions



Flow Curve TPE-FITTED



For additional information, please refer to the P2 Metal EOM.



P4 FDA SERIES

38 mm (1-1/2") PRO-FLO FDA SERIES METAL PUMP


Air Inlet: 1/2" FNPT
Tri-Clamp Inlet: 51 mm (2")
Tri-Clamp Discharge: 51 mm (2")




Max. Flow Rate:
330 lpm (87.2 gpm)
Max. Inlet Pressure:
8.6 bar (125 psig)
Max. Size Solids:
4.8 mm (3/16")

Max. Suction Lift:
6.4 m Dry (21.0')
9.3 m Wet (30.6')
Shipping Weight:
20 kg (45 lb)


Dimensions



Flow Curve TPE-FITTED



For additional information, please refer to the P4 Metal EOM.



51 mm (2") PRO-FLO FDA SERIES METAL PUMP

Air Inlet: 1/2" FNPT
Tri-Clamp Inlet: 64 mm (2-1/2")
Tri-Clamp Discharge: 64 mm (2-1/2")




Max. Flow Rate:
630 lpm (166 gpm)
Max. Inlet Pressure:
8.6 bar (125 psig)
Max. Size Solids:
6.4 mm (1/4")


Max. Suction Lift:
6.9 m Dry (22.7')
8.6 m Wet (28.4')
Shipping Weight:
51 kg (112 lb)

P8 FDA SERIES

Dimensions



Flow Curve^{TPE-FITTED}



For additional information, please refer to the P8 Metal EOM.



Notes

[illegible]



Hygienic

PSG Hygienic
Feldmühlenweg 6-10
D-49593 Bersenbrück
Germany
+49 5439 809210
psgdover.com/hygienic



Purity.
Performance.
Purpose.

HYG-150001-C-01-A4

Authorized PSG® Partner:

Copyright 2026 PSG®, a Dover company